



PURE WATER CLEANING SYSTEM

HPO HIGH PURE



PRESSURE

Mains Power Supply

FLOW RATE

Mains Power Supply

EXCLUSIVE CHARACTERISTICS

- ▶ POWER FILTER
- ▶ ERGONOMICS
- ▶ DURABILITY
- ▶ MANOMETER

TECHNICAL DATA

		HPO
Code		APTA40000
PERFORMANCE		
Operating pressure	bar	mains power supply
Pure water flow	l/min	mains power supply
Water in/out connections	gas	3/4"
Maximum working height	m	~10
Productivity	m ² /h	up to 150
Power supply		-
Absorbed power	kW	-
Dimension (LxWxH)	cm	53x50x127
Weight	kg	34

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/TENSILE STRUCTURES

STANDARD EQUIPMENT

CODE: FTAC40002
REVERSE OSMOSIS MEMBRANE



CODE: PRCH40034
POWDER FOR OSMOTIC MEMBRANE FILTER MAINTENANCE



CODE: KTRI40106
FILTER KIT: - 1 pcs sediment filter - 1 pcs active carbon filter - 1 pcs deionizing resin cartridge



CODE: TBFX40010
DRAINAGE TUBE



CODE: TBFX40009
30 m FLEXIBLE HOSE WITH FITTINGS



CODE: VVSF40018
FLOW REGULATION VALVE



CODE: AZMC40006
HAND-HELD TDS METER



CODE: CNPR40007
GASKET LUBRICANT

