



TASKI® Jontec Combi

F3a

Polymer based floor cleaner/maintainer

Description

A low foaming neutral detergent with polymers and waxes to give enhanced appearance and protection. Incorporates the O.N.T. (Odour Neutralising Technology) for effective malodour neutralisation and long lasting, fresh fragrance.

Key properties

- Perfect combination of detergents, polymers and waxes
- Low foaming and fast acting
- Leaves a protective film
- Fortifies the film after each application
- Unique, patented Odour Neutralizing Technology (O.N.T.)

Benefits

- Removes quickly and thoroughly water-soluble dirt and greasy soils and leaves a protective film on the floor
- Specially designed to be used in scrubber driers
- Neutralizes malodour molecules and therefore enhances the perfume effect
- Delivers a glossy protection, buffable for extra shine
- Builds up slip-resistant, protective film

Use Instructions

Manual/Machine cleaning:

1. Dose the product into the full water tank/bucket.
2. Apply the solution and remove the soiled solution.


Dosage*

TASKI Jontec Combi needs to be diluted.

- Dosage bucket: 50 ml / 5L (1%) Max 5%.
- Dosage scrubber drier: 100ml/10L (1%) Max 5%.

Proper dosage and temperature save costs and minimize environmental impacts.

**This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*



© A.I.S.E



TASKI® Jontec Combi

F3a

Technical data

Appearance:	Milky, white liquid
Odour:	Herbal
pH value (neat):	~ 8
pH value (in use):	~ 7
Relative density (g/cm ³ ; 20°C):	≈ 1.01

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

Product compatibility

Do not use on water sensitive floors, e.g. unsealed wood and cork.

Environmental information

The surfactants used in this product are biodegradable in compliance with the requirements of EC Directives 73/404/EEC and 73/405/EEC and their subsequent amendments.

Approvals

Slip resistance 0.5 minimum (ASTMD D 2047).

www.diversey.com

© 2023 Diversey, Inc. All Rights Reserved. 21/04/2023 en (P90839)