

Elifilm 5

Heavy duty alkaline cleaner

Description

Alkaline degreaser low foaming cleaner concentrated for vehicle cleaning, unprotected water-resistant hard floors and food, beverage and dairy industries.

Key properties

- High alkalinity and good emulsifying power
- Excellent degreaser suitable for all environment
- Medium foaming, fast acting and easy rinsing
- Versatile application
- Perfect for a floor care restoration and daily maintenance in retail market sector (ceramic tile)

Benefits

- Low foaming, safe for scrubber-driers
- Regardless the effective water hardness
- Removes the static vehicle film
- Gives a second life to your floors
- Absence of perfume makes it compatible with a food environment
- Effective on all types of food soiling
- Environmental responsible for waste water disposal and green surfactant

Use instructions

- 1. Manual:
 - Dose the product into a bucket filled with water and apply the solution.
 - Allow the product to act, then remove the soiled solution.

2. Machine:

- Dose the product into the full water tank of a single disc machine or a scrubber drier and apply the solution.
- Allow to act briefly and scrub, then remove the soiled solution.

3. Indirect method for heavy soil:

- Scrub the floor without wet vacuuming.
- Allow the product to act 5-10 minutes.
- Scrub a second time and directly wet vacuum the soiled solution.

Dosage:

Elifilm 5 needs to be diluted.

Dosage bucket: 1% (50 ml for 5L) max 3%.

Dosage scrubber drier: 1% (100 ml for 10 L) max 2,5% (3% to 5% for indirect method) Truck wash equipment: 1% max 3%.

High pressure: 0,2% max 1% (in lance/nozzle end – T°C: 15 to 70° C – pressure from 60 to 100 bars).

Foaming cleaner: 2% max 5% (T°C: 20°C – pressure from 60 to 100 bars).

Proper dosage and temperature save costs and minimize environmental impacts.

*This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.











Elifilm 5

Technical data

Appearance: Clear, slightly yellow-coloured liquid pH value (neat): +/- 11.5 pH value (in use): +/- 11.5 Relative density (20°C): 1.11 g/cm³ The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

Product compatibility

Do not use on alkali- and water-sensitive surfaces. Do not use on aluminium surfaces. Test material compatibility in a small inconspicuous place before use. Immediately remove any solution splashes from alkali-sensitive surfaces.

Environmental information

The surfactants used in this product are biodegradable in compliance with the requirements of EC Directives 73/404/EEC and 73/405/EEC and their subsequent amendments.

Available pack sizes

Elifilm 5 is available in 1x20L, 1x200L and 1x900L.