

Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name	:	Oasis Pro All Bath
Product code	:	116796E
Use of the Substance/Mixture	:	Sanitary cleaner
Substance type:	:	Mixture
		For professional users only.

Product dilution information : 1.0 % - 3.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	:	General purpose cleaner. Spray and wipe manual process Sanitary cleaner. Spray and wipe manual process
Recommended restrictions on use	:	Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company	 Ecolab Ltd. PO Box 11; Winnington Avenue Northwich, Cheshire, United Kingdom CW8 4DX + 44 (0)1606 74488 ccs@ecolab.com
	ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number	:	+441618841235 +32-(0)3-575-5555 Trans-European
Poison Information Centre telephone number	:	For medical professionals only: 0344 892 0111

Date of Compilation/Revision	:	30.07.2024
Version	:	4.1

Section: 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318

Specific target organ toxicity - single exposure, Category 3,
Respiratory systemH335Chronic aquatic toxicity, Category 3H412The classification of this product is based only on its extreme pH value (in accordance with current
European legislation).

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) Product AS SOLD Hazard pictograms :	No 1272/2008)	!
Signal Word :	Danger	
Hazard Statements :	H314 H335 H412	Causes severe skin burns and eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
Precautionary Statements :	Prevention:	
	P261 P273 P280 Response:	Avoid breathing vapours. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
	P273	Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
	P273 P280 Response:	Avoid release to the environment. Wear protective gloves/ eye protection/ face protection. 353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Hazardous components which must be listed on the label: monoethanolamine

Product AT USE DILUTION

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

2.3 Other hazards

Product AS SOLD

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD Hazardous components

Chemical Name	CAS-No. EC-No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
	REACH No.		. []
fatty alcohol alkoxylate	111905-52-3 POLYMER	Skin irritation Category 2; H315 Eye irritation Category 2; H319 Chronic aquatic toxicity Category 3; H412	>= 10 - < 20
Alcohols, C13, branched, ethoxylated	69011-36-5 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 5 - < 10
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335 Specific target organ toxicity - single exposure Category 3 H335 5 - 100 %	>= 5 - < 10
Isopropyl Alcohol	67-63-0 200-661-7 01-2119457558-25	Flammable liquids Category 2; H225 Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336 Serious eye damage/eye irritation Category 2 > 10 - 100 %	>= 2.5 - < 5
benzalkonium chloride	68424-85-1 939-253-5 01-2119965180-41	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10	>= 0.5 - < 1
		M(Chronic) = 1	

Product AT USE DILUTION Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
benzalkonium chloride	68424-85-1 939-253-5 01-2119965180-41	Acute toxicity Category 4; H302 Skin corrosion Category 1B; H314 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 1; H410 M = 10	>= 0.0025 - < 0.025
		M(Chronic) = 1	
Substances with a workp	lace exposure limit :	· · · · · · · · · · · · · · · · · · ·	
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Serious eye damage Category 1; H318	>= 0.25 - < 0.5

Isopropyl Alcohol 67-63-0 Flammable liquids Category 2; H225 >= 0.1 - < 200-661-7 01-2119457558-25 Specific target organ toxicity - single >= 0.25 Specific target organ toxicity - single exposure Category 3; H336 >= 0.1 - < Serious eye damage/eye irritation Category 2 > Category 2 > 10 - 100 % >			Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335 Specific target organ toxicity - single exposure Category 3 H335 5 - 100 %	
	Isopropyl Alcohol	200-661-7	Eye irritation Category 2; H319 Specific target organ toxicity - single exposure Category 3; H336 Serious eye damage/eye irritation Category 2	>= 0.1 - < 0.25

4.1 Description of first aid measures

at least 15	nediately with plenty of water, also under the eyelids, for 5 minutes. Remove contact lenses, if present and easy 1 tinue rinsing. Get medical attention immediately.
Wash clot	mmediately with plenty of water for at least 15 minutes. hing before reuse. Thoroughly clean shoes before t medical attention immediately.
anything t	uth with water. Do NOT induce vomiting. Never give by mouth to an unconscious person. Get medical mmediately.
If inhaled : Remove t if symptor	o fresh air. Treat symptomatically. Get medical attention ns occur.
Product AT USE DILUTION In case of eye contact : Rinse with	plenty of water.

in case of eye contact	
In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.
If inhaled	: Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

	Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
	Unsuitable extinguishing media	:	None known.	
5.2	Special hazards arising from	th	e substance or mixture	
	Specific hazards during firefighting	:	Fire Hazard Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.	
	Hazardous combustion products	:	Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) metal oxides	
5.3 Advice for firefighters				
	Special protective equipment for firefighters	:	Use personal protective equipment.	
	Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.	

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

 Advice for non-emergency personnel Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8. Advice for emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. Product AT USE DILUTION Advice for non-emergency personnel Advice for emergency responders Refer to protective measures listed in sections 7 and 8. If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. 6.2 Environmental precautions 		Product AS SOLD				
responders note of any information in Section 8 on suitable and unsuitable materials. Product AT USE DILUTION Advice for non-emergency personnel Advice for emergency responders : Refer to protective measures listed in sections 7 and 8. : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable 6.2 Environmental precautions		0,00	:	people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in		
Advice for non-emergency personnel Advice for emergency responders: Refer to protective measures listed in sections 7 and 8.: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.6.2 Environmental precautions		3 ,	:	note of any information in Section 8 on suitable and unsuitable		
personnel Advice for emergency : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. 6.2 Environmental precautions		Product AT USE DILUTION				
respondersnote of any information in Section 8 on suitable and unsuitable materials.6.2 Environmental precautions			:	Refer to protective measures listed in sections 7 and 8.		
•		U	:	note of any information in Section 8 on suitable and unsuitable		
•						
Product AS SOLD	6.2	Environmental precautions				
		Product AS SOLD				

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION		
Environmental precautions	:	No sp

: No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD Methods for cleaning up	: Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.
Product AT USE DILUTION Methods for cleaning up	: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information. For personal protection see section 8. See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD Advice on safe handling	Do not ingest. Do not get in eyes, on skin, or on clothing. Use of with adequate ventilation. Keep away from fire, sparks and hea surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Was hands thoroughly after handling. Do not breathe spray, vapour, case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (Pf	ated sh . In
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-us Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushi of the eyes and body in case of contact or splash hazard.	
Product AT USE DILUTION Advice on safe handling	Wash hands after handling. In case of mechanical malfunction, if in contact with unknown dilution of product, wear full Persona Protective Equipment (PPE). For personal protection see section 8.	al
Hygiene measures	Wash hands before breaks and immediately after handling the product.	

7.2 Conditions for safe storage, including any incompatibilities

Product AS SOLD Requirements for storage areas and containers Storage temperature	 Keep away from heat and sources of ignition. Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers. -5 °C to 40 °C
Product AT USE DILUTION Requirements for storage areas and containers	: Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep out of reach of children. Keep

container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-N	0.	Value type (Form of exposure)	Control parameters	Basis
monoethanolamine	141-43	-5	TWA	1 ppm 2.5 mg/m3	UKCOSSTD
Further information			be absorbed through the skin. The assigned substances are those for there are concerns that dermal absorption will lead to systemic toxicity.		
			STEL	3 ppm 7.6 mg/m3	UKCOSSTD
Further information	Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxici				
Isopropyl Alcohol	67-63-0)	STEL	500 ppm 1,250 mg/m3	UKCOSSTD
			TWA	400 ppm 999 mg/m3	UKCOSSTD

DNEL

oxydipropanol	: End Use: Workers
	Exposure routes: Inhalation
	Potential health effects: Long-term systemic effects
	Value: 238 mg/m3
	End Use: Workers
	Exposure routes: Dermal
	Potential health effects: Long-term systemic effects
	Value: 84 mg/cm2
	End Use: Consumers
	Exposure routes: Inhalation
	Potential health effects: Long-term systemic effects
	Value: 70 mg/m3
	End Use: Consumers
	Exposure routes: Dermal

Potential health effects: Long-term systemic effects Value: 51 mg/cm2
End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 24 ppm

PNEC

oxydipropanol	: Fresh water
	Value: 0.1 mg/l
	Marine water
	Value: 0.01 mg/l
	Fresh water
	Value: 1 mg/l
	Value. Tilligh
	Intermittent use/release
	Value: 2 mg/l
	Fresh water sediment
	Value: 0.238 mg/kg
	Mania a sa disa sa t
	Marine sediment
	Value: 0.0238 mg/kg
	Sewage treatment plant
	Value: 1000 mg/l
	C C
	Soil
	Value: 0.0253 mg/kg
	Oral
	Value: 313 mg/kg

8.2 Exposure controls

Product AS SOLD Appropriate engineering controls			
Engineering measures	: Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.		
Individual protection measur	es		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.		
Eye/face protection (EN 166)	: Safety goggles Face-shield		

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Oasis Pro All Bath				
Hand protection (EN 374)	 Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. 			
Skin and body protection (EN 14605)	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes			
Respiratory protection (EN 143, 14387)	: When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P			
Product AT USE DILUTION Appropriate engineering cor	ntrols			
Engineering measures	: Good general ventilation should be sufficient to control worker			
5 5	exposure to airborne contaminants.			
Individual protection measu	res			
Hygiene measures	: Wash hands before breaks and immediately after handling the product.			
Eye/face protection (EN 166)	: No special protective equipment required.			
Hand protection (EN 374)	: No special protective equipment required.			
Skin and body protection (EN 14605)	: No special protective equipment required.			
Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.			
Environmental exposure co	Environmental exposure controls			
General advice	: Consider the provision of containment around storage vessels.			
Section: 9. PHYSICAL AND CHE	MICAL PROPERTIES			
9.1 Information on basic physica	al and chemical properties			

Product	AS	SOLD	
---------	----	------	--

Appearance

Colour	:	: orange light orange	
Odour	:	slight	odourized
рН	:	11.4 - 12.4, 100 %	10.4 - 10.9
Flash point	:	45 °C, Does not sustain combust	ion.
Odour Threshold	:	Not applicable and/or not determine	ined for the mixture
Melting point/freezing point	:	Not applicable and/or not determine	ined for the mixture
Initial boiling point and boiling range	:	Not applicable and/or not determine	ined for the mixture
Evaporation rate	:	Not applicable and/or not determine	ined for the mixture
Flammability (solid, gas)	:	Not applicable and/or not determine	ined for the mixture
Upper explosion limit	:	Not applicable and/or not determine	ined for the mixture
Lower explosion limit	:	: Not applicable and/or not determined for the mixture	
Vapour pressure	:	: Not applicable and/or not determined for the mixture	
Relative vapour density	:	Not applicable and/or not determine	ined for the mixture
Relative density	:	: 1.015 - 1.02	
Water solubility	:	: soluble	
Solubility in other solvents	:	Not applicable and/or not determine	ined for the mixture
Partition coefficient: n- octanol/water	:	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	:	Not applicable and/or not determine	ined for the mixture
Thermal decomposition	:	Not applicable and/or not determine	ined for the mixture
Viscosity, kinematic	:	Not applicable and/or not determine	ined for the mixture
Explosive properties	:	Not applicable and/or not determine	ined for the mixture
Oxidizing properties	:	The substance or mixture is not o	lassified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Acids

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials: Carbon oxides nitrogen oxides (NOx) metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD Information on likely routes of exposure	:	Inhalation, Eye contact, Skin contact
Product		
Acute oral toxicity	:	Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	:	4 h Acute toxicity estimate : > 5 mg/l Test atmosphere: dust/mist
Acute dermal toxicity	:	Acute toxicity estimate : > 2,000 mg/kg
Skin corrosion/irritation	:	There is no data available for this product.
Serious eye damage/eye irritation	:	There is no data available for this product.
Respiratory or skin sensitization	:	There is no data available for this product.
Carcinogenicity	:	There is no data available for this product.
Reproductive effects	:	There is no data available for this product.
Germ cell mutagenicity	:	There is no data available for this product.
Teratogenicity	:	There is no data available for this product.
STOT - single exposure	:	There is no data available for this product.
STOT - repeated exposure	:	There is no data available for this product.
Aspiration toxicity	:	There is no data available for this product.
Components		
Acute oral toxicity	:	fatty alcohol alkoxylate LD50 rat: > 2,000 mg/kg
		Alcohols, C13, branched, ethoxylated LD50 rat: > 500 mg/kg
		monoethanolamine LD50 rat: 1,089 mg/kg
		Isopropyl Alcohol LD50 rat: 4,710 mg/kg

	nzalkonium chloride LD50 rat: 344 mg/kg	
Components		
Acute inhalation toxicity	onoethanolamine 4 h LC50 rat: > 1.6 mg/l est atmosphere: dust/mist	
	opropyl Alcohol 4 h LC50 rat: 30 mg/l est atmosphere: vapour	
Components		
Acute dermal toxicity	onoethanolamine LD50 rabbit: 1,025 mg/kg	
	opropyl Alcohol LD50 rabbit: 12,870 mg/kg	
	nzalkonium chloride LD50 rabbit: 3,340 mg/kg	
Potential Health Effects		
Product AS SOLD Eyes	auses serious eye damage.	
Skin	auses severe skin burns.	
Ingestion	auses digestive tract burns.	
Inhalation	ay cause respiratory tract irritation. May cause	nose throat and
minalation	ng irritation.	
Chronic Exposure	ealth injuries are not known or expected under	normal use.
Product AT USE DILUTION Eyes	ealth injuries are not known or expected under	normal use.
Skin	ealth injuries are not known or expected under	
Ingestion	ealth injuries are not known or expected under	normal use.
Inhalation	ealth injuries are not known or expected under	normal use.
Chronic Exposure	ealth injuries are not known or expected under	
Experience with human expo	,	
Product AS SOLD		
Eye contact	edness, Pain, Corrosion	
Skin contact	edness, Pain, Corrosion	
Ingestion	prrosion, Abdominal pain	
Inhalation	espiratory irritation, Cough	
Product AT USE DILUTION Eye contact	o symptoms known or expected.	
Skin contact	o symptoms known or expected.	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Ingestion	: No symptoms known or expected.
Inhalation	: No symptoms known or expected.
ction: 12. ECOLOGICAL INFO	RMATION
1 Toxicity	
Product AS SOLD Environmental Effects	: Harmful to aquatic life with long lasting effects.
Product AT USE DILUTION Environmental Effects	: This product has no known ecotoxicological effects.
Product AS SOLD Product	
Toxicity to fish	: no data available
Toxicity to daphnia and other aquatic invertebrates	: no data available
Toxicity to algae Components	: no data available
Toxicity to fish	: fatty alcohol alkoxylate96 h LC50 Leuciscus idus (Golden orfe): mg/l
	Alcohols, C13, branched, ethoxylated96 h LC50 Fish: 3 mg/l
	Isopropyl Alcohol96 h LC50 Fish: 9,640 mg/l
Components	
Toxicity to daphnia and other aquatic invertebrates	: fatty alcohol alkoxylate48 h EC50 Daphnia magna (Water flea): mg/l
	Alcohols, C13, branched, ethoxylated48 h EC50 Daphnia magn (Water flea): 1.5 mg/l
	monoethanolamine48 h EC50 Aquatic Invertebrate: 65 mg/l
	Isopropyl Alcohol24 h EC50 Daphnia magna (Water flea): 9,714 mg/l
	benzalkonium chloride48 h EC50 Daphnia magna (Water flea): 0.016 mg/l
2 Persistence and degradabil	ity
Product	
Biodegradability	: The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC
Components	
components	
Biodegradability	: fatty alcohol alkoxylateResult: Readily biodegradable.

monoethanolamineResult: Readily biodegradable.

Isopropyl AlcoholResult: Readily biodegradable.

benzalkonium chlorideResult: Biodegradable

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste.Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD Product :	Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility.
Contaminated packaging :	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
Guidance for Waste Code : selection	Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.
Product AT USE DILUTION	

Product	: Diluted product can be flushed to sanitary sewer if regulations

permit.

Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

: 2491
: ETHANOLAMINE, SOLUTION
: 8
: 111
: No
: None
: 2491
: Ethanolamine solution
: 8
: 111
: No
: None
: 2491
: ETHANOLAMINE SOLUTION
: 8
: 111
: No
: None
: Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents	: 15 % or over but less than 30 %: Non-ionic surfactants	
Regulation EC 648/2004	less than 5 %: Anionic surfactants, Cationic surfactants	
-	Other constituents: Perfumes	

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major- accident hazards involving dangerous substances.	:	FLAMMABLE LIQUIDS P5c Lower tier : 5,000 t Upper tier : 50,000 t
Candidate List of Substances of Very High Concern for Authorisation	:	Not applicable.

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations	:	The Chemicals (Hazard Information and Packaging for Supply) Regulations.
		The Control of Substances Hazardous to Health Regulations. Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment
Specific target organ toxicity - single exposure 3, H335	Calculation method
Chronic aquatic toxicity 3, H412	Calculation method

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada);

ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by

: Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: General purpose cleaner. Spray and wipe manual process

Life Cycle Stage	:	Widespread use by professional workers	
Product category	:	PC35	Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release	:	ERC8a	Wide dispersive indoor use of processing aids in open
category			systems

Daily amount per site	:	7.5 kg		
Type of Sewage Treatment Plant	:	Municipal s	ewage treatment plant	
Contributing scenario contro	ollir	ng worker ex	posure for:	
Process category	:	PROC10	Roller application or brushing	
Exposure duration	:	480 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exha	ust Ventilation is not required	
General ventilation		Ventilation	rate per hour	1
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	

Contributing scenario controlling worker exposure for:

Process category	:	PROC8a	Transfer of substance or preparation (charg discharging) from/ to vessels/ large contained dedicated facilities	
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exha	ust Ventilation is not required	
General ventilation		Ventilation	rate per hour	1
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	
Contributing scenario contr	olliı	ng worker ex	xposure for:	
Process category	:	PROC11	Non industrial spraying	
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		

Local Exhaust Ventilation is not requiredGeneral ventilationVentilation rate per hour1Skin Protection:see section 8Respiratory Protection:see section 8

Exposure Scenario: Sanitary cleaner. Spray and wipe manual process

Life Cycle Stage	:	Widespread use by professional workers	
Product category	:	PC35	Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category	:	ERC8a	Wide dispersive indoor use of processing aids in open systems
Daily amount per site	:	7.5 kg	
Type of Sewage Treatment Plant	:	Municipal s	ewage treatment plant

Contributing scenario controlling worker exposure for:

Process category	:	PROC10	Roller application or brushing	
Exposure duration	:	480 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exha	ust Ventilation is not required	
General ventilation		Ventilation I	rate per hour	1
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	

Contributing scenario controlling worker exposure for:

Process category	:	PROC8a	Transfer of substance or preparation (chargin discharging) from/ to vessels/ large container dedicated facilities	•
Exposure duration	:	60 min		
Operational conditions and risk management measures	:	Indoor		
		Local Exha	ust Ventilation is not required	
General ventilation		Ventilation	rate per hour	1
Skin Protection	:	see section	8	
Respiratory Protection	:	see section	8	
Contributing scenario contr	olliı	ng worker ex	xposure for:	

Process category	:	PROC11	Non industrial spraying
Exposure duration	:	60 min	

Operational conditions and risk management measures	:	Indoor
		Local Exhaust Ventilation is not required
General ventilation		Ventilation rate per hour
Skin Protection	:	see section 8
Respiratory Protection	:	see section 8

1