

UNBLOCKING AGENT



- Easy to use.
- Elevated penetrating and lubricating power.
- Anti-corrosion effect.



SUGGESTIONS

After having sprayed generously, it is advisable to wait for a few minutes before intervening.

DESCRIPTION

An unblocking and protective spray containing oils with elevated lubricating and penetrating properties. Allows for the easy unblocking of screws, nuts and bolts blocked by rust, dirt, dried oily residues etc. ST1 has elevated penetrating properties which allow it to reach the most inaccessible of points. Its elevated lubricating properties reduce friction and increase ease of movement for moving parts, gears, hinges, locks etc. Parts treated with ST1 remain covered with an oily film which protects from corrosion and prevents further blockages in the short term. It quickly penetrates: it softens dirt and corrosion, unblocking oxidised joints, nuts, bolts, linkages and metal parts. It protects against oxidation: after the evaporation of the solvents, it forms a protective barrier which is capable of preventing new blocks, guaranteeing effective protection against rust and corrosion.

ST 1 SPRAY

UNBLOCKING AGENT

PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	Spray can
Colour of active ingredient	Pale yellow
Fragrance	Naphthenic
Specific weight of active ingredient	0.880 ± 0.01 g/ml
Solubility in water	Indissoluble
pH	Non-applicable
Pressure at 20°C	3.3 ± 0.5 bar
Inflammability	Highly inflammable

None

AVAILABLE PACKAGING

Box of 12 cans - 400ml each - 016SVIS0012

USE MODALITY

Spray directly on the parts concerned and wait for a few moments in order to allow the product to act, before proceeding with unblocking.

For particularly resistant cases repeat the operation until the block is freed.

The product maintains its properties when properly stored in an unopened package, in a cool and dry place away from light and heat sources, at a temperature between 5°C and 35°C.

Rev. 01 Ed. 01/17