

ALKALINE DETERGENT FOR THE CLEANING OF CAR EXTERIORS



- Guarantees a perfect clean.
- Easy to rinse with anti-stain properties.
- Restores a natural shine to bodywork.



SUGGESTIONS

In order to obtain the best results, it is necessary to work, when possible, in the shade, without allowing the product to dry on surfaces: spray evenly from below in an upwards movement. On heated surfaces proceed with cooling with water before spraying the detergent solution.

DESCRIPTION

A concentrated product for the cleaning of car exteriors with a spray system or with a high-pressure water jet. An alkaline detergent which, as well as its notable detergent, sequestrant, shining and anti-settling characteristics, is also easy to rinse and has anti-stain properties, thanks to its prolonged wetting action. Ideal for the removal of stubborn dirt typically caused by heavy-duty traffic (smog), from trucks, tankers, cars and tarpaulins without the use of brushes. Ideal for the pre-washing of cars before entering in tunnel system car washes. Its outstanding degreasing properties furthermore allow for the perfect cleaning of particularly dirty industrial flooring, mechanical parts and metal surfaces.

ALKALINE DETERGENT FOR THE CLEANING OF CAR EXTERIORS

PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	Clear liquid
Colour	Pale yellow
Fragrance	Light characteristic
Specific weight	1.130 ± 0.01 g/ml
Solubility in water	Complete in all ratios
pH	>13
Chemical properties	Anionic - cationic

pH 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14

Moderate

AVAILABLE PACKAGING

20 Kg container - 016TFRSTN20

USE MODALITY

Washing without brushes:

Dilute TFR Super 1:40 - 1:50 with water. Spray evenly and rinse under high pressure. In some cases, when the dirt is particularly thick, pre-washing with water only is recommended in order to remove the worst of the dirt, followed by spraying with the detergent solution and rinsing under high pressure.

Pre-washing of cars before entering tunnel systems:
Dose 15-20 ml per vehicle

Washing with a high-pressure jet cleaner:

Dilute to 10% with water and draw the solution obtained directly with the high-pressure water jet. Pass evenly over the entire surface and rinse thoroughly.

FOR PROFESSIONAL USE ONLY.

The product maintains its properties when properly stored in an unopened package, in a cool and dry place away from light and heat sources, at a temperature between 5°C and 35°C.

CORRELATED PRODUCTS ACCESSORIES

Nebulizzatore 25L
01AA720001

