

VIRTUAL 3000 SOFT

allegriini.
CARWASH & CAR CARE

ALKALINE CONCENTRATED DETERGENT FOR THE EXTERNAL WASHING OF VEHICLES THROUGH NEBULIZER SYSTEM OR HIGH PRESSURE WASHER



- Ideal for the external washing of vehicles through nebulizer system or high pressure wash
- Specially designed for the removal of stubborn dirt typically caused by heavy-duty traffic.
- Easy to rinse.



SUGGESTIONS

Do not allow the product to dry on surfaces; work, when possible, in the shade: spray evenly from below in an upwards movement. On heated surfaces proceed with cooling with water before spraying the detergent solution. It is recommended to respect the dilutions of use. Do not use in concentrated solution on aluminium or light leagues.

DESCRIPTION

VIRTUAL 3000 SOFT is a concentrated product ideal for the external washing of vehicles through nebulizer system or high pressure washer. As well as its notable detergent, sequestrant, shining and anti-settling characteristics, is also easy to rinse and, thanks to its prolonged wetting action, it has anti-stain properties. Specially for the removal of stubborn dirt typically caused by heavy-duty traffic (smog). Excellent for the pre-washing of cars before entering in tunnel system car washes.

ALKALINE CONCENTRATED DETERGENT FOR THE EXTERNAL WASHING OF VEHICLES THROUGH NEBULIZER SYSTEM OR HIGH PRESSURE WASHER

PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance	Clear liquid
Colour	Fluorescent green
Odour	Slightly citrus
Specific weight	1.150 ± 0.015 g/ml
Solubility in water	Complete in all ratios
pH	> 13
Chemical properties	Anionic - no ionic



High

AVAILABLE PACKAGING

20Kg container - 016VIRSTN20

USE MODALITY

WASHING WITHOUT BRUSHES:

Dilute VIRTUAL 3000 SOFT in a ratio between 1:30 and 1:70 with water. Spray evenly and rinse under high pressure. In some cases, when the dirt is particularly thick, prewashing with water only is recommended in order to remove the worst of the dirt, followed by spraying with the detergent solution and rinsing under high pressure.

PRE-WASHING OF CARS BEFORE ENTERING TUNNEL

SYSTEMS:

Dilute VIRTUAL 3000 SOFT in a ratio between 1:40 and 1:60 with water, nebulize homogeneously and let the vehicle enter in the tunnel. In case of dirt such as mud, it is recommended to prewash with high pressure water before entering the carwash tunnel in order to prevent scratches on paint.

WASHING WITH A HIGH-PRESSURE JET CLEANER:

Dilute VIRTUAL 3000 SOFT in a ratio between 1:10 and 1:30 with water. Adjust the suction dosage, pass evenly over the entire surface and rinse thoroughly.

AUTOMATIC CAR WASH:

Dose 10-25 ml of the product per vehicle.

FOR PROFESSIONAL USE ONLY.

The product maintains its properties when properly stored in an unopened package, in a cool and dry place away from light and heat sources, at a temperature between 5°C and 35°C.


ALKALINE CONCENTRATED DETERGENT FOR THE EXTERNAL WASHING OF VEHICLES THROUGH NEBULIZER SYSTEM OR HIGH PRESSURE WASHER

CORRELATED PRODUCTS ACCESSORIES

Nebulizzatore 25L
01AA720001



Nebulizzatore 50L



Nebulizzatore 100L

